

Technical specifications:

- ▶ Protection class IP66
- ▶ Seamlessly foamed-in 2-component polyurethane gasket
- ▶ Impact resistance IK08 (DIN EN 50102:1997-09)
- ▶ Glass-fibre reinforced polycarbonate in colour black RAL 9005
- ▶ UV-resistant (UL 746C F1)
- ▶ Self-extinguishing (UL 94 V0) in colour black
- ▶ Flammability classification UL 94 V2 with transparent cover

May we introduce?!

MBI BLACK

THE HIDDEN CHAMPION - Strikingly invisible



Cover in black or transparent

With knockouts or plain sides

Additional MBI sizes available +500 pcs

Key features MBI Black:

- ▶ Systematic focus on requirements in industrial installations
- ▶ Ideally suitable for use in industrial and outdoor applications
- ▶ Enclosure bases with metric pre-formed knockouts or plain side walls
- ▶ Individual side designs with mould inserts
- ▶ Corrosion-free plastic cover screws
- ▶ Variety of mounting points in the enclosure base
- ▶ Various fixing options on walls or machines
- ▶ Ideal for hidden installations

Type	Length mm	Width mm	Height mm
MBI-PC BK 090706	94	65	57
MBI-PC BK 111107	110	110	66
MBI-PC BK 130906	130	94	57
MBI-PC BK 180906	180	94	57
MBI-PC BK 181309	180	130	90
MBI-PC BK 181809	182	180	90
MBI-PC BK 251811	254	180	111